

- 1. PRE-CAST BOX, SEAT, AND LID SHALL BE CHRISTY CONCRETE PRODUCT MODEL G5 TRAFFIC VALVE BOX OR APPROVED EQUAL.
- 2. SURFACE OF LID SHALL BE LABELED "MONUMENT" ENGRAVED IN 1" HIGH LETTERS.
- 3. BRASS MARKER DISC SHALL BE ENGRAVED WITH RESPONSIBLE LICENSED SURVEYOR OR CIVIL ENGINEER REGISTRATION NO. AND MONUMENT POINT PUNCHED.
- 4. CONCRETE SHALL BE CLASS "A".
- 5. PLACE CONCRETE FOR MONUMENT IN DRILLED HOLE.
- 6. LOCKING GRADE RINGS (NOT SHOWN) SHALL BE INSTALLED WITH 3/8"X1" NC BOLT AND JAM NUT (IN 3 PLACES) WHEN STREET IS RESURFACED TO BRING MONUMENT LID FLUSH WITH NEW FINISHED GRADE.

LOCKING GRADE RINGS		
CHRISTY NO.	DESCRIPTION	
G5GR10 G5GR15	1" HIGH CAST IRON 1-1/2" HIGH CAST IRON	
G5GR20	2" HIGH CAST IRON	



DRAWN BY:	K. TRAN
CHECKED BY:	F. AMIN
APPROVED BY:	G. GOMEZ
DATE: OC	TOBER 2013

OCTOBER 2013

MONUMENT

ST-20

CITY OF SANTA CLARA

PAGE: 20